## Warm Audio WA273-EQ Specs

| Rack Height            | 2 RU  |
|------------------------|---|
| Number of Channels     | 2   |
| Inputs                 | 2 x XLR 3-pin (balanced)<br>2 x 1/4" TRS (balanced)<br>2 x 1/4" TS (unbalanced) |
| Outputs                | 2 x XLR 3-pin (balanced)<br>2 x 1/4" TRS (balanced)                             |
| Phantom Power          | 48 V  |
| High-Pass Filter       | Off, 50 Hz, 80 Hz, 160 Hz, or 300 Hz  |
| Gain Range             | Up to 80 dB   |
| Frequency Response     | 20 Hz to 20 kHz (±0.5 dB)   |
| Equivalent Input Noise | -111 dBu (unweighted)   |
| Power Requirement      | 115/230 V, 50/60 Hz   |
| Dimensions (W x D x H) |   |
|                        | 19.0 x 3.5 x 11.0" / 48.3 x 8.9 x 27.9 cm                                       |
| Weight                 | 19.0 x 3.5 x 11.0" / 48.3 x 8.9 x 27.9 cm  16 lb / 7.3 kg                       |

2 x 1/4" TS insert returns 2 x 5-segment LED meters Switches for phantom power, polarity, impedance, input source, insert, power, and ground lift

## Packaging Info

| Package Weight         | 19.25 lb         |
|------------------------|------------------|
| Box Dimensions (LxWxH) | 24 x 15.4 x 5.6" |