

Image Sensor	CIS x 2
Optical Resolution	600 dpi
Hardware Resolution	600 x 600 dpi
Scan Modes	Color: 48-bit Input; 24-bit Output Grayscale: 16-bit Input; 8-bit Output B/W: 1-bit
Scanning Speed	Duplex: 2 sec (Color Mode, 300 dpi, A4) Note: Scanning speed varies, depending upon the scanning software, CPU and RAM of PC.
Scanning Area (W x L)	Max. 216 x 594 mm (8.5" x 23.38") Std: 210 x 297 mm (8.27" x 11.69")
Acceptable Paper Sizes (W x L)	Max.: 218 x 594 mm (8.58" x 23.38") Min.: 88 x 54 mm (3.46" x 2.13")
Acceptable Paper Weight (Thickness)	Paper: 50 g/m ² to 250 g/m ² Plastic card: Non-Embossed up to 1 mm & Embossed up to 1.24 mm (ISO 7810)
Daily Duty Scan (Sheets)	1000
Other Function	Multi Auto-Detection (Hardware): - Auto-Feed Detection

	- Document Feeding Skew Detection - Paper Jam Detection - Lid Uncovered Detection - Motor Stalled Detection
Power Supply	AC Power: 24V / 1.25A
Power Consumption	Operating: Max. 18.5W Idle: Max. 4.5W
Interface	USB 2.0
Net Weight	1.12 Kgs (2.49 Lbs)
Dimensions (W x D x H)	289 x 90.7 x 60.7 mm (11.38" x 3.57" x 2.39")
Protocol	TWAIN compliant (Option)
OS	Windows Vista / 7 / 8 / 10 LINUX SANE for Systems Integrator. Please contact local sales.
Hardware Requirements	Pentium® IV 2.4 GHz processor One available USB 2.0 Port 1GB RAM (2GB or higher recommended) 1GB free HDD space (2GB or larger recommended)
Operating Environments	Temperature: +5°C to +45°C Relative Humidity: 20% to 80% RH (No condensation)