Basic Specs

Dusic Opecs	
FUNCTIONS	PRINTER TYPE
Fax, Print, Scan, Copy	Laser Printer
PRINT SPEED	PAPER SIZE
Up to 36 pages/minute (Letter size) Up to 34 pages/minute (A4 size)	A4, Letter, A5, A5(Long Edge), A6, Executive, Legal, Folio, Mexico Legal, Ir
Print	
RESOLUTION	2-SIDED - PAPER TYPE
600 x 600 dpi HQ1200 (2,400 x 600 dpi) quality 1,200 x 1,200 dpi	Plain Paper, Thin Paper, Recycled Paper
2-SIDED - PAPER SIZE	
A4	
Print Media	
PAPER INPUT - PAPER TRAY #1 - PAPER TYPE	PAPER INPUT - PAPER TRAY #1 - MAXIMUM PAPER CAPACIT
Plain Paper, Thin Paper, Recycled Paper	Up to 250 sheets of 80 g/m2 plain paper
PAPER INPUT - MULTI-PURPOSE TRAY	PAPER OUTPUT
1 sheet	Up to 120 sheets of 80 g/m2 plain paper (face-down delivery to the face-down tray)
Сору	
MONOCHROME	MULTIPLE COPIES
Yes	Sorts - Yes. Stacks up to 99 pages.
ENLARGE/REDUCE	RESOLUTION
25% to 400% (in increments of 1%)	Up to 600 x 600 dpi
2-SIDED - PAPER TYPE	2-SIDED - PAPER SIZE
Plain Paper, Thin Paper, Recycled Paper	A4
Connectivity	
USB	LAN
USB 2.0	10BASE-T / 100BASE-TX
WIRELESS LAN	NFC
IEEE 802.11b/g/n (Infrastructure/Ad-hoc Mode) IEEE 802.11g/n (Wi-Fi Direct)	Yes

Scan

Stan	
COLOUR SCANNING	MONOCHROME
Yes	Yes
COLOUR DEPTH - INPUT	COLOUR DEPTH - OUTPUT
30 bit colour Processing	24 bit colour Processing
GREYSCALE - INPUT	GREYSCALE - OUTPUT
10 bit colour Processing	8 bit colour Processing
RESOLUTION - INTERPOLATED	RESOLUTION - SCANNER GLASS
Up to 19200 × 19200 dpi	Max 1200 x 1200 dpi
RESOLUTION - ADF	
Max. 600 x 600 dpi	
Fax	
MODEM SPEED	GREYSCALE - COLOUR
33,600 bps	8bit / 256 levels
GROUPS	BROADCASTING
Up to 20	258 Locations
SPEED DIAL	AUTOMATIC REDIAL
200 locations	Yes
MEMORY TRANSMISSION	OUT OF PAPER RECEPTION
Up to 500 pages	Up to 500 pages
Display & Memory	
DISPLAY	MEMORY CAPACITY
2.7" Touchscreen LCD	256 MB
Operation	
POWER SOURCE	POWER CONSUMPTION - PRINTING
220 - 240 V AC 50/60 Hz	Average: Approx. 475W
POWER CONSUMPTION - READY	POWER CONSUMPTION - SLEEP
Average: Approx. 42W	Average: Approx. 6.4W

POWER CONSUMPTION - POWER OFF

Approx. 0.03W

NOISE LEVEL

LpAm = 49 dB(A)

Supported OS

WINDOWS® OPERATING SYSTEM

Windows 7 SP1, 8, 8.1, 10, Server 2008 (Network only), Server 2008 R2 (Network only), Server 2012 (Network only), Server 2012 R2 (Network only), 10, Server 2016 (Network only)

MAC OPERATING SYSTEM

OS X v10.10.5, 10.11.x,10.12.x (Download only)

LINUX OPERATING SYSTEM

CUPS, LPD/LPRng (x86/x64 environment)