

2042 Cable Locator



Receiver

Fluke 2042

The multipurpose solution to cable location

The Fluke 2042 is a professional general purpose cable locator. It is ideal for tracing cables in walls and underground, locating fuses/breakers on final circuits and locating interruptions and short-circuits in cables and electrical floor heating systems. It can also be used for tracing metallic water and heating pipes. The unit is supplied as a complete kit comprising of a transmitter and receiver in a purpose-made carry case. The receiver also incorporates a torch function for working in dimly lit locations.

- For all applications (live or dead cables) without additional instruments
- Set includes a transmitter and a receiver
 Proven digitally coded sender signal
- guarantees clear signal identification
- Transmitter with LCD-display for transmitting level, transmitting code and external voltage

- Receiver with a backlight LCD-display for level of receiving signal, code of receiving signal and live voltage indication
- Automatic or manual adjustment of receiving signal sensitivity
- Switchable acoustic receiving signal
 Auto-Power-Off
- Additional torch lamp function for working in dark environments
- Additional transmitters are available for extension or to distinguish between several signals.

Specifications

0...2.5m wall/underground

Receiver

cables 0...0.4m





Included Accessories

TL27 Heavy Duty Test Lead Set (2) TP74 Lantern Tip Test Probe Set AC285 Alligator Clip Set Soft carrying case Hard case

Ordering Information

Fluke 2042 Cable Loc (transmitt Fluke 2042T Cable Loc

Cable Locator (transmitter + receiver) Cable Locator Transmitter



Voltage Measurement Range

Tracing depth cable location

Batteries Transmitter: 6 pc Batteries 1.5V Batteries Receiver: 1 pc Battery 9V Size (HxWxD) Transmitter: 190 mm x 85 mm x 50 mm Size (HxWxD) Receiver: 250 mm x 65 mm x 45mm Weight Locator: 0.45 kg Weight Receiver: 0.36 kg Two Year Warranty

Main voltage detection

Frequency Range

Output signal

Voltage

Location of fuses/breakers and assignment to circuits



Transmitter

0 60Hz

125 kHz

Up to 400V AC/DC

12V, 50V, 120V, 230V, 400V

Tracing of underground cables (max. depth 2.5 m)





Precise location of cable interruptions with additional transmitter

Recommended Accessories



11079-eng Rev. 03

Fluke 2042T