

## Hyper 212X RR-212X-20PM-R1



#### Features

- High performance Copper heatpipes with a fusion bonded copper powder wick.
- Patented CDC<sup>™</sup> technology 4 direct touch heatpipes creating a gap-less contact surface
- Aluminum Fin Array with New Tunnel Effect layout for improved heat dissipation.
- 4<sup>th</sup> Generation Bearing MTBF of 160,000 hours thanks to highly durable POM components.
- Redesigned Fan-blades that create vortices to boost airflow without creating more noise
- Smart Fan engine stops the fan when blocked to prevent damage, and automatically restarts the fan when it has been cleared.
- Universal mounting system for all Intel and AMD platforms.

### Package Information

| EAN Code           | 4719512039526              |
|--------------------|----------------------------|
| UPC Code           | 884102018862               |
| Package Dimensions | 90 x 157 x 228 mm          |
|                    | (3.5 x 6.2 x 9.0 inch)     |
| Carton Dimensions  | 475 x 330 x 255 mm         |
|                    | ( 18.7 x 13.0 x 10.0 inch) |
| Unit / Carton      | 10                         |
| Carton / Pallet    | 42                         |

The CoolerMaster Hyper 212X introduces several new features to the incredibly popular 212 series. It uses the same Patented Quad CDC Heatpipe array but features a completely new cooling fan and an improved fin-blade layout. Thanks to the new Smart Engine and 4<sup>th</sup> Generation Bearing, the MTBF has been pushed up to an incredible 160,000 hours while reducing bearing noise. The redesigned Fan-Blades and Aluminum Fin-Blades have both been optimized to create micro vortices that boost the airflow and circulate it around the heatpipes.

#### **Specifications**

|  | Intel LGA 2011/1366/1156/1155/775   |
|--|---|
| Supported Platforms  | AMD FM1/AM3+/AM3/AM2  |
| Dimensions   | 120 x 79 x 158 mm (4.7 x 3.1 x 6.2 inch)  |
| Heatsink Dimensions  | 116 x 51 x 158 mm (4.6 x 2.0 x 6.2 inch)  |
| Heatsink Material  | 4 Direct contact heatpipes / Aluminum fins  |
| Heatsink Weight  | 492g / 1.1lb  |
| Heatpipe Dimensions  | Ø6 mm   |
| Fan Dimensions   | 120 x 120 x 25 mm (4.7 x 4.7 x 1 inch)  |
| Fan Speed  | 600~2000 RPM (PWM) ± 10%  |
| Fan Air Flow   | 24.9~82.9 CFM ± 10%   |
|  |   |
| Fan Air Pressure   | 0.3~2.09 mm H <sub>2</sub> O ± 10%  |
| Fan Air Pressure<br>Fan Life Expectancy  | 0.3~2.09 mm H <sub>2</sub> O ± 10%<br>160,000 hours   |
|  | -   |
| Fan Life Expectancy  | -<br>160,000 hours  |
| Fan Life Expectancy<br>Noise Level   | -<br>160,000 hours<br>9~36 dBA  |
| Fan Life Expectancy<br>Noise Level<br>Bearing Type                               | 160,000 hours<br>9~36 dBA<br>4 <sup>th</sup> Generation Bearing                             |
| Fan Life Expectancy<br>Noise Level<br>Bearing Type<br>Connector                  | 160,000 hours<br>9~36 dBA<br>4 <sup>th</sup> Generation Bearing<br>4-Pin                    |
| Fan Life Expectancy<br>Noise Level<br>Bearing Type<br>Connector<br>Rated Voltage | 160,000 hours<br>9~36 dBA<br>4 <sup>th</sup> Generation Bearing<br>4-Pin<br>12 VDC          |
| Fan Life ExpectancyNoise LevelBearing TypeConnectorRated VoltageRated Current    | 160,000 hours<br>9~36 dBA<br>4 <sup>th</sup> Generation Bearing<br>4-Pin<br>12 VDC<br>0.37A |

Warranty

2 years



# Appendix

Photo taken: July, 2012



Note: Photos may differ slightly from the final product.