

Revitalizing how businesses deliver content and differentiate themselves in any viewing environment is what Samsung's QEN series displays provide. With brilliant content delivery through UHD picture quality and its large size, this digital signage offers a one-of-a-kind experience for all viewers. The QEN series is not only an affordable display, but it is also reliable and built to last. In addition, the QEN series will turn any space into a contemporary setting with its boundless and slim-edge design.

# **Highlights**

- Deliver content effectively through reliable yet cost-efficient digital displays
- Provide a captivating viewing experience with 82" large-sized screen
- Elevate content quality through a unique combination of picture-enhancing features
- Amplify graphic performance within the powerful TIZEN operating system
- Create an inviting, sophisticated space with a sleek design
- · Facilitate secure, PC-free meetings through rigid three-layer protection

## **Industry trend**

Businesses are looking for ways to present clear and effective messaging to its audiences while improving their customer experience. Turning to large-sized displays with UHD picture quality allows businesses to provide engaging content on a stable device. Not only looking for digital signage that is large with distinct content, businesses want displays that are versatile and can meet operational changes over time.

## Why Samsung QEN series?

Samsung QEN Series leverages Samsung's Intelligent Picture Quality technology to elevate content delivery in any setting. This refined presentation transforms content from any source to UHD-level quality, and optimizes on-screen text and imagery with crisp edges and fine detail. Recent advancements have made the signage offerings even stronger and empower businesses to develop and deploy content with the confidence that it will perform continuously. Users are assured information being presented is clear, engaging and easy to see due to its large size. With a modern and sophisticated design, the QEN series can easily be integrated to any environment.





### **Intelligent Picture Quality**



# **Key features**





#### Powerful Performance

- Graphic performance with Quad core CPU
- UHD Content play back - HTML5 Compatibility



### **Easy Development**

- Tizen Studio - Node.JS HTTP web Server



#### **Business Expandability**

- Remote Management Signage Device Management
- Enhanced Security

### Streamline operational efficiency

The embedded MagicINFO Player S6, backed by the powerful TIZEN operating system, boosts the displays overall performance, allows for painless content management and ensures seamless content transition and playback.



## Elevate visual appeal in any setting

Bezel-less on three sides, the QEN Series displays transform any meeting space into a visually appealing experience that is unique and welcoming. Featuring a modern slim-edge design, the QEN Series brings flexible style to any environment.



### **Empower secure and remote collaboration**

Samsung's KNOX platform provides rigid three-layer protection while also securing and controlling USB and user network exchange through dedicated signage device management. With added security, businesses can facilitate remote, PC-free meetings without risk or complexity.

# **Specifications**

	Model		QE82N
	D: 10:	Class	82
	Diagonal Size	Measured	81.5"
	Туре		120Hz Edge
	Resolution		UHD (3840 x 2160)
	Pixel Pitch (mm)		0.15675 x 0.047025
	Active Display Area		1805.76(H) x 1015.74(V)
Panel	Brightness(Typ.)		300
unce	Contrast Ratio (Typ.)		5000:1
	Viewing Angle(H/V)		178/178
	Response Time (G to G)		6ms (Max 15ms)
	Display Colors		16.7M
	Color Gamut		72%
	Operation Hour		16/7
	Haze		2%
Display	Dynamic C/R		MEGA
	H-Scanning Frequency		30 ~ 81kHZ
risplay	V-Scanning Frequency		48 ~ 75HZ
	Maximum Pixel Frequency		594MHz
ound	Speaker Type		Built in Speaker(10W 2CH + 20W Woofer)
	-peaner type	RGB	
			DVI-D
		VIDEO	HDMI 2.0 (2)
	INPUT	HDCP	HDCP 2.2
		AUDIO	Stereo Mini Jack, DVI/HDMI/Audio(Common)
		USB	USB 2.0 x 2
		RGB	N/A
Connectivity		VIDEO	N/A
connectivity	ОИТРИТ		
		AUDIO	Stereo Mini Jack
		Power Out	N/A
		USB	N/A
	EXTERNAL CONTROL		RS232C(in/out) thru stereo jack, RJ45
	EXTERNAL SENSOR		N/A
	Tuner		N/A
	Туре		Internal
Power	Power Supply		AC100 - 240 V~ (+/-10 %), 50/60 Hz
	Power Consumption	Max[W/h]	325
		Typical[W/h]	237
		Rating[W/h]	295
		Sleep mode	less than 0.5W
		Off mode	less than 0.5W
	Dimension(mm)	Off mode Set	less than 0.5W 1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)
	Dimension(mm)	Off mode Set Package	less than 0.5W 1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand) 2017 x 1222 x 295
		Off mode Set	less than 0.5W 1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)
Mechanical	Dimension(mm) Weight (kg)	Off mode Set Package	less than 0.5W 1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand) 2017 x 1222 x 295
		Off mode Set Package Set	less than 0.5W 1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand) 2017 x 1222 x 295 44.4 / 45.5 (with Stand)
	Weight (kg) VESA Mount	Off mode Set Package Set	less than 0.5W 1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand) 2017 x 1222 x 295 44.4 / 45.5 (with Stand) 60.4 600*400
	Weight (kg) VESA Mount Protection Glass	Off mode Set Package Set	less than 0.5W 1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand) 2017 x 1222 x 295 44.4 / 45.5 (with Stand) 60.4 600*400 N/A
	Weight (kg) VESA Mount Protection Glass Stand Type	Off mode Set Package Set Package	less than 0.5W 1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand) 2017 x 1222 x 295 44.4 / 45.5 (with Stand) 60.4 600*400 N/A Foot Stand (Inbox)
	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo	Off mode Set Package Set Package	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less
pec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo  Operating Temperature	Off mode Set Package Set Package	less than 0.5W  1830.0 × 1054.0 × 60.9 / 1830.0 × 1144.6 × 387.2 (with Stand)  2017 × 1222 × 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C−40°C
Spec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo  Operating Temperature  Humidity	Off mode Set Package Set Package	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less
Spec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo  Operating Temperature	Off mode Set Package Set Package	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C−40°C
Mechanical Spec Operation	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo Operating Temperature Humidity Key	Off mode Set Package Set Package	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C-40°C  10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0
Spec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo  Operating Temperature  Humidity	Off mode Set Package Set Package ot) (mm)	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C- 40°C 10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi
Spec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo Operating Temperature Humidity Key	Off mode Set Package Set Package ot) (mm)  H/W S/W	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C - 40°C 10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"
Spec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo Operating Temperature Humidity Key	Off mode Set Package Set Package ot) (mm)  H/W S/W Processor	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C- 40°C  10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU
Spec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo Operating Temperature Humidity Key	Off mode Set Package Set Package ot) (mm)  H/W S/W Processor On-Chip Cache Memory	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C- 40°C 10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB
Operation	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo Operating Temperature Humidity Key	Off mode Set Package Set Package ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C- 40°C  10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB  1.7GHz
operation	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special	Off mode Set Package Set Package ot) (mm)  H/W S/W Processor On-Chip Cache Memory	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C - 40°C  10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A72 1.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB
pec	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special	Off mode Set Package Set Package ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C - 40°C  10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 3ZKB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR4 1.5GHz 64bit
operation	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C - 40°C 10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UJ, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 3ZKB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR41.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)
operation	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special	Off mode Set Package Set Package  Ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM)	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C - 40°C 10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 3ZKB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by 0/S, 4.12GB Available)
operation	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C- 40°C  10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 3ZKB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by 0/S, 4.12GB Available)  *Video Decoder : MPEG-172/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9
pec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo Operating Temperature Humidity Key  Special	Off mode Set Package Set Package  Ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM)	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C - 40°C  10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 3ZKB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by O/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, UC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : ACS (DD), MPEG
pec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo Operating Temperature Humidity Key  Special	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C-40°C 10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A72.1.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by O/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : AC3 (DD), MPEG  USB 2.0
pec	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Booperating Temperature Humidity Key Special  Internal Player (Embedded H/W)	Off mode Set Package Set Package  Ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600.4  600.4  600.4  700 N/A  Foot Stand (Inbox)  3 Bezel-less  0°C - 40°C  10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR41.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by 0/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, U-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : AC3 (DD), MPEG  USB 2.0  Tizen 4.0 (VDLinux)
pec	Weight (kg)  VESA Mount  Protection Glass  Stand Type  Bezel Width (Top/Side/Bo Operating Temperature Humidity Key  Special	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C- 40°C  10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by O/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : AC3 (DD), MPEG  USB 2.0  Tizen 4.0 (VDLinux)  CB (Europe) : IEC60065/EN60065KC(Korea) : K 60065RCM(Australia) : IEC60065/AS/NZ5 60065TUV (Germany) : CENEMKO (Norw.
peration	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special  Internal Player (Embedded H/W)	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C- 40°C 10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UJ, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by 0/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : AC3 (DD), MPEG  USB 2.0  Tizen 4.0 (VDLinux)  CB (Europe) : IEC60065/EN60065KC(Korea) : K 60065RCM(Australia) : IEC60065/AS/NZS 60065TUV (Germany) : CENEMKO (Norw.
peration	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bc Operating Temperature Humidity Key Special  Internal Player (Embedded H/W)  Safety EMC	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C- 40°C 10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)*  Coretex A72.1.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4.1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by O/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : AC (DD), MPEG USB 2.0  Tizen 4.0 (VDLinux)  CB (Europe) : IEC60065/EN60065KC(Korea) : K 60065RCM(Australia) : IEC60065/AS/NZS 60065TUV (Germany) : CENEMKO (Norw. CLass A
peration	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special  Internal Player (Embedded H/W)  Safety EMC Environment	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (lnbox)  3 Bezel-less  0°C- 40°C  10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)*  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  86B (3.88GB Occupied by 0/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : AC3 (DD), MPEG  USB 2.0  Tizen 4.0 (VDLinux)  CB (Europe) : IEC60065/EN60065KC(Korea) : K 60065RCM(Australia) : IEC60065/AS/NZS 60065TUV (Germany) : CENEMKO (Norwalias)
operation Seature	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bc Operating Temperature Humidity Key Special  Internal Player (Embedded H/W)  Safety EMC	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports Operating System	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less 0°C- 40°C 10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A72.1.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by O/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : AC (DD), MPEG USB 2.0  Tizen 4.0 (VDLinux)  CB (Europe) : IEC60065/EN60065KC(Korea) : K 60065RCM(Australia) : IEC60065/AS/NZS 60065TUV (Germany) : CENEMKO (Norwa
Operation Teature	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special  Internal Player (Embedded H/W)  Safety EMC Environment	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (linbox)  3 Bezel-less  0°C- 40°C  10~80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)"  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  86B (3.88GB Occupied by 0/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder: AC3 (DD), MPEG  USB 2.0  Tizen 4.0 (VDLinux)  CB (Europe) : IEC60065/EN60065KC(Korea) : K 60065RCM(Australia) : IEC60065/AS/NZS 60065TUV (Germany) : CENEMKO (Norwalics)
Spec	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special  Internal Player (Embedded H/W)  Safety EMC Environment Included	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports Operating System	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C- 40°C  10-80%  UHD Signage Display, Slim & Light Signage with, Built-in MagicInfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)*  Coretex A72 1.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by 0/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : ACS (DD), MPEG  USB 2.0  Tizen 4.0 (VDLinux)  CB (Europe) : IEC60065/EN60065KC(Korea) : K 60065RCM(Australia) : IEC60065/AS/NZS 60065TUV (Germany) : CENEMKO (Norwa: CE Class A  Yes  Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries
Operation  Feature  Certification	Weight (kg)  VESA Mount Protection Glass Stand Type Bezel Width (Top/Side/Bo Operating Temperature Humidity Key Special  Internal Player (Embedded H/W)  Safety EMC Environment	Off mode Set Package Set Package  ot) (mm)  H/W S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports Operating System	less than 0.5W  1830.0 x 1054.0 x 60.9 / 1830.0 x 1144.6 x 387.2 (with Stand)  2017 x 1222 x 295  44.4 / 45.5 (with Stand)  60.4  600*400  N/A  Foot Stand (Inbox)  3 Bezel-less  0°C- 40°C  10-80%  UHD Signage Display, Slim & Light Signage with, Built-in Magicinfo S6, SSSP 6.0  Built in Speaker(10W 2ch + 20W Woofer), Wi-Fi  Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)*  Coretex A721.7GHz Quad-Core CPU  L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB  1.7GHz  2.5GB, LPDDR4 1.5GHz 64bit  Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)  8GB (3.88GB Occupied by 0/S, 4.12GB Available)  *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9  *Audio Decoder : ACS (DD), MPEG  USB 2.0  IZEA 4.0 (VDLinux)  CB (Europe) : IEC60065/EN60065KC(Korea) : K 60065RCM(Australia) : IEC60065/AS/NZS 60065TUV (Germany) : CENEMKO (Norwa : CE Class A  Yes  Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries  N/A (Inbox)

#### About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, cameras, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

#### **SMART Signage**

For more information about Samsung SMART Signage Ben Series Displays, visit www.samsung.com/business or www.samsung.com/displaysolutions

Copyright © 2018 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd. 416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea

