Product specifications

Functions

Print, copy, scan, fax, digital send, easy access USB dri stapler, (optional advanced digital send, wireless)

Printer page yield	Declared yield value in accordance with ISO/IEC 19798. Actual yields vary considerably based on images printed and other factors. For more information visit http://www.hp.com/go/learnaboutsupplies
First page out (ready) black	As fast as 10.5 sec
First page out (ready) color	As fast as 10.5 sec
Resolution (black)	Up to 1200 x 1200 dpi
Resolution (color)	Up to 1200 x 1200 dpi
Resolution technology	HP ImageREt 3600, Pantone Calibrated
Monthly duty cycle	Up to 80,000 pages Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
Recommended monthly page volume	2000 to 6000 ^[5]
Print Technology	Laser
Display	8.0" (20.3 cm) touchscreen, SVGA LCD (color graphics)
Number of print cartridges	4 (1 black, cyan, magenta, yellow)
Replacement cartridges	HP 507A Black LaserJet Toner Cartridge (yield ~5500 pages) CE400A; HP 507X Black LaserJet Toner Cartridge (yield ~11,000 pages) CE400X; HP 507A Cyan LaserJet Toner Cartridge (yield ~6000 pages) CE401A; HP 507A Yellow LaserJet Toner Cartridge (yield ~6000 pages) CE402A; HP 507A Magenta LaserJet Toner Cartridge (yield ~6000 pages) CE403A

Print languages	HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.4)
Automatic paper sensor	No
Paper trays, standard	2
Paper trays, maximum	3
Mobile Printing Capability	HP ePrint; Apple AirPrint™; Mopria™-certified
Connectivity, standard	2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host; 1 Fax
Connectivity, optional	802.11b/g/n wireless LAN (station mode), other networking accessories, HP Jetdirect 2700w USB Wireless Print Server
Network ready	Standard (built-in Gigabit Ethernet)
Ports	2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host; 1 Fax
Security management	Management security: SNMPv3, SSL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in; Compatible with HP Imaging & Printing Security Center
Minimum system requirements	Mac OS X v10.6, 10.7; 200 MB available hard disk space; operating system compatible hardware system requirements, see http://www.apple.com Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 R2; 200 MB available hard disk space; operating system compatible hardware system requirements, see microsoft.com
Compatible operating systems	Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008 (32 and 64-bit), Windows Server 2008 R2 (64-bit); Mac OS X v10.5, 10.6, 10.7; For the latest operating system support see: Citrix and Windows Terminal Services (hp.com/go/upd); Novell (novell.com/iprint); Linux (hplip.net); UNIX (hp.com/go/unix,

	hp.com/go/unixmodelscripts, hp.com/go/jetdirectunix_software); SAP device types (hp.com/go/sap/drivers, hp.com/go/sap/print); HP ePrint Mobile Driver (hp.com/go/eprintmobiledriver)
Memory card compatibility	None
Memory, standard	1536 MB
Memory, maximum	1536 MB
Printer management	HP Web Jetadmin, HP Utility (Mac)
Print speed, color (draft)	Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
Supported network protocols	IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print
Hard disk	Standard, embedded HP High-Performance Secure Hard Disk, minimum 320 GB; AES 256 hardware encryption or greater; Secure erase capabilities (Secure File Erase-Temporary Job Files, Secure Erase-Job Data, Secure ATA Erase-Disk)
Paper handling input, standard	100-sheet multipurpose tray, 250-sheet input tray 2, 100-sheet automatic document feeder
Paper handling output, standard	250-sheet face-down output bin, convenience stapler
Duplex printing	Automatic (standard)
Envelope input capacity	Up to 10 envelopes
Finished output handling	Sheetfed
Media sizes supported	Tray 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 16K, 10 x 15 cm, postcard (JIS), DPostcard (JIS), envelopes (B5, C5, C6, DL); Tray 2: A4, A5, B5 (JIS), 16K; Optional 500-sheet tray 3: A4, A5, RA4, B5 (JIS), 16K; Automatic Two-sided

	Printing Unit: A4, A5, RA4, B5 (JIS), 16K
Media sizes, custom	Tray 1: 3×5 in to 8.5×14 in; Tray 2: 5.8×8.3 in to 8.5×11.7 in; Optional Tray 3: 5.8×8.3 in to 8.5×14 in; Automatic Two-sided Printing Unit: 5.8×8.3 in to 8.5×14 in
Media types	Paper (bond, color, letterhead, light, plain, preprinted, prepunched, recycled, rough, mid-weight, heavy, extra heavy, mid-weight glossy, heavy glossy, extra heavy glossy); envelopes, labels, cardstock, card glossy, transparencies, opaque film, user-defined
Supported media weight	Tray 1: 16 to 58 lb (plain paper); 28 to 58 lb (glossy paper); Tray 2: 16 to 43 lb (plain paper); 28 to 58 lb (glossy paper); Optional Tray 3: 16 to 47 lb (plain paper); 28 to 58 lb (glossy paper)
Media weights by paper path	Tray 1: 60 to 216 g/m² (plain paper), 105 to 220 g/m² (glossy paper); Tray 2: 60 to 163 g/m² (plain paper), 105 to 220 g/m² (glossy paper); Optional Tray 3: 60 to 176 g/m² (plain paper), 105 to 220 g/m² (glossy paper); automatic two-sided printing unit: 60 to 163 g/m² (plain paper), 105 to 220 g/m² (glossy paper)
Power	Input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 12 A
Print speed, black (normal)	Up to 31 ppm
Power consumption	655 watts (Printing), 665 watts (Copying), 52 watts (Ready), 11.3 watts (Sleep), 0.99 watts (Auto-Off), 0.3 watts (Off)
Energy efficiency	ENERGY STAR® qualified; EPEAT® Silver
Operating temperature range	50 to 81°F
Operating humidity range	20 to 60% RH
Dimensions (W X D X H)	21.6 x 21.8 x 23 in
Dimensions Maximum (W X D X H)	36.7 x 24.8 x 23 in (tray 1 open with legal extension, keyboard extended)
Weight	105 lb
Package weight	116.4 lb

What's in the box	HP LaserJet Enterprise color flow MFP M575c; Power cord; HP LaserJet Toner Cartridges, 1 Black (~5500 pages), 1 each Magenta, Cyan, Yellow (~6000 pages); Software and documentation on CD-ROM; Installation guide; Support flyer; Fax cable
Print speed, color (normal)	Up to 31 ppm
Cable included	No, please purchase USB cable separately
Warranty	One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to http://www.hp.com/support to learn about HP award winning service and support options in your region.
Software included	Windows Installer, HP PCL 6 discrete driver, Mac Installer, HP Postscript emulation driver
FCC	FCC Class A emissions - for use in commercial environments, not residential environments